



SOCKET HEAD CAP SCREWS  
 6-32 X  $\frac{3}{8}$  - 2 REQ'D.  
 6-32 X  $\frac{1}{2}$  - 1 "  
 10-32 X  $\frac{1}{2}$  - 1 "


SHOULDER BOLTS  
 $\frac{5}{16}$  ( $\frac{1}{4}$ -20) X  $\frac{1}{2}$  - 2 REQ'D.  
 $\frac{5}{16}$  ( $\frac{1}{4}$ -20) X  $\frac{5}{8}$  - 3 "  
 $\frac{5}{16}$  ( $\frac{1}{4}$ -20) X  $\frac{1}{2}$  - 1 "



VALVE SPRING-EXHAUST  
 .045 WIRE  
 PART # 156



VALVE SPRING-INLET  
 .040 WIRE  
 PART # 155



GOVERNOR SPRING  
 .025 WIRE - 3 REQ'D.  
 PART # 154

SPRINGS MAY BE PURCHASED  
 AT MOST HARDWARE STORES  
 AND CUT TO LENGTH.

J & E PALMER CAMPBELL, CALIF.			
SCALE: FULL	APPROVED BY:	DRAWN BY: V.S.P.	
DATE: 6/85		REVISED:	
THE J & E JUNIOR HIT & MISS ENGINE			
ASSEMBLY		DRAWING NUMBER 11 OF 12	